

#121


ULTRA HIGH SPEED POLISH

This polish is designed especially for the demanding conditions created by today's high speed and ultra high speed maintenance systems. Whether using 175 - 3500 rpm this product is a proven performer that adapts to your maintenance program. This scientifically developed product produces a "flash-cured", thermoplastic reaction resulting in an ultra wet-look with superior gloss and durability. This tough finish resists scuffs, scratches, and black heel marks while providing a truly beautiful, slip-free surface. The beauty in every floor is brought out with the very first coat of this superior floor polish. Each coat increases the depth of crystal clear gloss. Truly a finish for the 21st century!

This unique product is recommended for use on vinyl composition, vinyl asbestos, asphalt, linoleum, rubber, sealed cork, sealed wood, marble, terrazzo, concrete and slate flooring. It is compatible with and will adhere to almost all finishes and sealed surfaces.

SPECIFICATIONS

Total Solids	21+/- .5%, ASTM D1289-64
Appearance	Milky white emulsion
Coverage	2000 - 3000 sq. ft./gal
Gloss	Superior
Water Resistance.....	Excellent, ASTM D1793-66
Film Color.....	StabilityExcellent - Will not yellow with age
Slip Resistance.....	Excellent. Classified as slip resistant.
.....	ASTM D2047-64
Powdering Resistance	Excellent
Resistance to Scuffing / Scratching.....	Outstanding
Dry Time	20 - 40 minutes



HAWK SOLUTIONS

P.O. Box 29925 / Dallas, TX 75229 / 800-999-8652