

# EXECUTIVE

## Floor Polish

This high gloss metal-interlock, "dry bright" finish is formulated with the latest floor finish polymers, resins and waxes. Formulated for a greater degree of protection and durability, this anti-slip surface outwears other, ordinary finishes. The superb traffic fighting qualities of this polish gives it outstanding black heel mark, scuffing and detergent resistance.

Other characteristics that make this the finish of choice are:

**DURABILITY** - Consistent for a prolonged period, under vastly varying circumstances (surface type, traffic level, application, climate).

**GLOSS** - Produces a high, clear gloss from the first coat.

**SLIP RESISTANCE** - By its very nature, this floor finish offers a high coefficient of friction making it less slippery.

**LEVELING** - Flows smoothly and evenly contributing to increased coverage and high gloss.


**REMOVABILITY** - Excellent removability is maintained over a prolonged period of time.

All types of flooring respond beautifully to this modern floor coating. Use in every location, at all types of facilities. An excellent choice for vinyl, asbestos, tile, rubber, linoleum, sealed wood, marble, terrazzo and all composition floors.

### Specifications & Test Methods

Total Solids.....	18.5 +/- .5	ASTM D 1289-64
pH.....	8.8+/- .2	ASTM E 70-68
Sediment.....	Less than 0.1%	ASTM D 1290-57
Gloss.....	Specular gloss of not less than 90.	ASTM D 1455-64
Removal.....	Readily removed with conventional and re-emulsifying strippers	
Water Resistance.....	24 hours after application, polish does not show adverse effects such as whitening when water is applied for 1 hour.	ASTM
Slip Resistance.....	Excellent.	
	Classified as slip-resistant floor material when tested by methods of	ASTM D 204-64T
Coverage.....	2500 - 3000 sq.ft. per gallon	
Dry Time.....	Average 20 - 30 minutes per coat.	

FOR MORE INFORMATION PLEASE CALL 800-999-8652



**HAWK SOLUTIONS**

P.O. Box 29925 / Dallas, TX 75229 / 800-999-8652