

METAL COAT

PROTECTIVE COATING

This product is designed to protect metal and metal parts from oxidation and corrosion. The saturated paraffin coating is solvent based and dries quickly for long term protection. It is safe for use on all metals, for storage indoors or outdoors and will not crack, peel or chip. Dust and dirt can be wiped off without disturbing the coating surface.


The coating will adhere better and is most effective if the surface is first prepared clean and dry. It may be applied by dipping, wiping, brushing and spraying. For more severe storage conditions, a second coat can be applied within minutes. The protective coatings can be removed by submerging object in boiling point hot water (212°F) or easily with a cloth, wet with mineral spirits, kerosene or spirit blend.

Keep this product away from heat or flame and do not smoke during use of this product. Do not take internally and keep away from children.

SPECIFICATIONS

Color	Off white, milky
Odor	Characteristic / Solvent
Diluent	Spirity Blend
Boiling Point	282°F
Type Coating	Saturated Paraffin
Flash Point / Liquid	165°F
Dry Time / Tack Free	Approx. 20 min. @ room temp.
Dry Time / Complete Set	Approximately 2 hours

KEEP OUT OF REACH OF CHILDREN!



HAWK SOLUTIONS

P.O. Box 29925 / Dallas, TX 75229 / 800-999-8652