

# WATER EMULSION SEAL


## Water-Based Permanent Seal

This water-based acrylic resin seal dries to a slip free, high gloss finish. The dry film produced by this product is extremely durable and can be considered a permanent seal. It is highly chemical and detergent resistant and withstands extreme abuse from soil and pedestrian and forklift traffic. It effectively seals and protects all masonry surfaces such as, concrete (old and new), terrazzo, marble, brick, quarry tile, stone and other similar surfaces.

Water Emulsion Seal can be applied with a lint free mop by anyone familiar with floor finish application. There is no need to acid etch the floor in preparation before applying this product. The floor needs to be clean and dry prior to application as the clear film produced by this formulation will show any impurities in/on the surface. The more porous the surface the faster the product will absorb into the floor. Multiple coats will build sealer from within the floor to the surface of the floor - producing increasing surface gloss. Allow the floor to dry thoroughly between coats. Dry time will vary with environmental conditions such as temperature, humidity, and circulation, as well as with the amount of finish put down. Coverage is normally 1000 to 1500 square feet per gallon. Highly porous floors may require heavier applications.

### SPECIFICATIONS

Type of Product .....	Acrylic Resin
Color .....	White Emulsion
Color of Dry Film.....	Water Clear
% Solids.....	20 ± .5%
Flash Point .....	Non-Flammable
Slip Resistance .....	Classified as Slip Resistant
Gloss.....	Excellent



**HAWK SOLUTIONS**

P.O. Box 29925 / Dallas, TX 75229 / 800-999-8652